December 4th, 2017

DECLARATION OF PERFORMANCE

According to Annex III to Regulation (EU) no. 305/2011

Nº 17.004

1. Unique identification code of the product-type:

Biosphere Premium

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

EN 1504-2:2004

Surface protection systems for concrete, flexible system

Coating. Use for moisture control

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Industria Española para el Desarrollo e Investigación 2100, S.A. Pol. Ind. Poliviso, c/ Herreros 8, 41520 El Viso del Alcor, Sevilla, España

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Non-relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+ (4)

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

ALL WORLD CERTIFICATION. Avda Benjamin Franklin, 19, 46980, Paterna, Valencia, Spain. Notified agency No. 1170. I have performed the factory inspection and inspection of the production of the factory itself, as well as the current supervision, evaluation and rating of production controls of the factory according to system +2 (4) and issues the certificate

Graphenstone | IEdiSa, S.A. Polg Ind Poliviso. Carpinteros, 25. 41520 El Viso del Alcor, Sevilla. España (Spain). Phone: +34 955 529 435

























THE ORIGINAL AND AUTHENTIC

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Non-relevant

9. Declared performance

Technical properties	Performance	Normalized technical specifications
Bond strength by pull-off	≥0.8 N/mm ²	UNE-EN 1504-2
Water vapor permeability	Clase I	UNE-EN 1504-2
Capillary absorption and liquid water permeability	w < 0.10 kg/m²⋅min ^{0,5}	UNE-EN 1504-2
Fire behaviour	A1	UNE-EN 1504-2

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Antonio León Jiménez

President & CTO Graphenstone























